

bron color SCORO A4S : 閃光時間変動データ (1灯での変化)

SCORO A4S(ver.37.06) :3200Ws~3Ws

Ws	総出力	閃光最短	選択範囲	選択範囲	選択範囲	閃光最適	選択範囲	選択範囲	選択範囲	選択範囲	閃光最長
3200	10	1/132				1/132					1/132
2983	9.9	1/132				1/132					1/132
2786	9.8	1/162				1/162					1/162
2599	9.7	1/187				1/187					1/187
2425	9.6	1/200				1/200					1/200
2263	9.5	1/230				1/215					1/215
2111	9.4	1/250				1/250			1/250		1/125
1970	9.3	1/285				1/250			1/250		1/125
1838	9.2	1/305				1/265			1/250		1/125
1715	9.1	1/325				1/285			1/250	1/125	1/115
1600	9	1/375				1/305			1/250	1/125	1/115
1493	8.9	1/405				1/325			1/250	1/125	1/115
1393	8.8	1/435				1/350			1/250	1/125	1/108
1300	8.7	1/500			1/500	1/375			1/250	1/125	1/108
1213	8.6	1/535			1/500	1/405			1/250	1/125	1/100
1131	8.5	1/575			1/500	1/435			1/250	1/125	1/100
1056	8.4	1/615			1/500	1/435			1/250	1/125	1/100
985	8.3	1/655			1/500	1/465			1/250	1/125	1/100
919	8.2	1/750				1/500		1/500	1/250	1/125	1/100
857	8.1	1/810				1/535		1/500	1/250	1/125	1/100
800	8	1/875				1/575		1/500	1/250	1/125	1/100
746	7.9	1/935				1/615		1/500	1/250	1/125	1/100
696	7.8	1/1000		1/1000		1/615		1/500	1/250	1/125	1/100
650	7.7	1/1070		1/1000		1/655		1/500	1/250	1/125	1/100
606	7.6	1/1150		1/1000		1/700		1/500	1/250	1/125	1/100
566	7.5	1/1230		1/1000		1/700		1/500	1/250	1/125	1/85
528	7.4	1/1310		1/1000		1/750		1/500	1/250	1/125	1/85
493	7.3	1/1400		1/1000		1/810		1/500	1/250	1/125	1/85
460	7.2	1/1500		1/1000		1/810		1/500	1/250	1/125	1/85
429	7.1	1/1630		1/1000		1/875		1/500	1/250	1/125	1/85
400	7	1/1750		1/1000		1/875		1/500	1/250	1/125	1/85
373	6.9	1/1870		1/1000		1/875		1/500	1/250	1/125	1/85
348	6.8	1/2000	1/2000	1/1000		1/935		1/500	1/250	1/125	1/85
325	6.7	1/2150	1/2000	1/1000		1/935		1/500	1/250	1/125	1/85
303	6.6	1/2300	1/2000			1/1000	1/1000	1/500	1/250	1/125	1/85
283	6.5	1/2450	1/2000			1/1070	1/1000	1/500	1/250	1/125	1/85
264	6.4	1/2620	1/2000			1/1070	1/1000	1/500	1/250	1/125	1/85
246	6.3	1/2800	1/2000			1/1150	1/1000	1/500	1/250	1/125	1/85
230	6.2	1/2800	1/2000			1/1150	1/1000	1/500	1/250	1/125	1/85
214	6.1	1/3000	1/2000			1/1230	1/1000	1/500	1/250	1/125	1/85
200	6	1/3250	1/2000			1/1230	1/1000	1/500	1/250	1/125	1/85
187	5.9	1/3500	1/2000			1/1310	1/1000	1/500	1/250	1/125	1/85
174	5.8	1/3750	1/2000			1/1310	1/1000	1/500	1/250	1/125	1/85
162	5.7	1/3750	1/2000			1/1310	1/1000	1/500	1/250	1/125	1/85

bron color SCORO A4S : 閃光時間変動データー (1灯での変化)

SCORO A4S(ver.37.06) :3200Ws~3Ws

Ws	総出力	閃光最短	選択範囲	選択範囲	選択範囲	閃光最適	選択範囲	選択範囲	選択範囲	選択範囲	選択範囲	閃光最長
152	5.6	1/4000		1/4000	1/2000	1/1310		1/1000	1/500	1/250	1/125	1/85
141	5.5	1/4300		1/4000	1/2000	1/1310		1/1000	1/500	1/250	1/125	1/85
132	5.4	1/4600		1/4000	1/2000	1/1310		1/1000	1/500	1/250	1/125	1/85
123	5.3	1/4900		1/4000	1/2000	1/1310		1/1000	1/500	1/250	1/125	1/85
115	5.2	1/4900		1/4000	1/2000	1/1310		1/1000	1/500	1/250	1/125	1/100
107	5.1	1/5250		1/4000	1/2000	1/1310		1/1000	1/500	1/250	1/125	1/115
100	5	1/5600		1/4000	1/2000	1/1400		1/1000	1/500	1/250		1/132
93.3	4.9	1/6000	1/6000	1/4000	1/2000	1/1400		1/1000	1/500	1/250		1/140
87.1	4.8	1/6000	1/6000	1/4000	1/2000	1/1400		1/1000	1/500	1/250		1/162
81.2	4.7	1/6500	1/6000	1/4000	1/2000	1/1500		1/1000	1/500	1/250		1/175
75.8	4.6	1/7000	1/6000	1/4000	1/2000	1/1500		1/1000	1/500	1/250		1/187
70.7	4.5	1/7000	1/6000	1/4000	1/2000	1/1630		1/1000	1/500	1/250		1/215
66	4.4	1/7500	1/6000	1/4000	1/2000	1/1630		1/1000	1/500	1/250		1/230
61.6	4.3	1/8000	1/6000	1/4000	1/2000	1/1630		1/1000	1/500			1/250
57.4	4.2	1/8000	1/6000	1/4000	1/2000	1/1630		1/1000	1/500			1/265
53.6	4.1	1/8000	1/6000	1/4000	1/2000	1/1750		1/1000	1/500			1/305
50	4	1/8000	1/6000	1/4000	1/2000	1/1750		1/1000	1/500			1/325
46.7	3.9	1/8000	1/6000	1/4000	1/2000	1/1870		1/1000	1/500			1/350
43.5	3.8	1/8000	1/6000	1/4000	1/2000	1/1870		1/1000	1/500			1/375
40.6	3.7	1/8000	1/6000	1/4000	1/2000	1/1870		1/1000	1/500			1/405
37.9	3.6	1/8000	1/6000	1/4000		1/2000	1/2000	1/1000	1/500			1/435
35.4	3.5	1/8000	1/6000	1/4000		1/2000	1/2000	1/1000	1/500			1/465
33	3.4	1/8000	1/6000	1/4000		1/2150	1/2000	1/1000				1/500
30.8	3.3	1/8000	1/6000	1/4000		1/2000	1/2000	1/1000				1/535
28.7	3.2	1/8000	1/6000	1/4000		1/2150	1/2000	1/1000				1/575
26.8	3.1	1/8000	1/6000	1/4000		1/2150	1/2000	1/1000				1/615
25	3	1/8000	1/6000	1/4000		1/2300	1/2000	1/1000				1/700
23.3	2.9	1/8000	1/6000	1/4000		1/2300	1/2000	1/1000				1/750
21.8	2.8	1/8000	1/6000	1/4000		1/2300	1/2000	1/1000				1/810
20.3	2.7	1/8000	1/6000	1/4000		1/2450	1/2000	1/1000				1/875
18.9	2.6	1/8000	1/6000	1/4000		1/2450	1/2000	1/1000				1/935
17.7	2.5	1/8000	1/6000	1/4000		1/2620	1/2000					1/1000
16.5	2.4	1/8000	1/6000	1/4000		1/2800	1/2000					1/1070
15.4	2.3	1/8000	1/6000	1/4000		1/2800	1/2000					1/1150
14.4	2.2	1/8000	1/6000	1/4000		1/3000	1/2000					1/1230
13.4	2.1	1/8000	1/6000	1/4000		1/3000	1/2000					1/1400
12.5	2	1/8000	1/6000	1/4000		1/3250	1/2000					1/1500
11.7	1.9	1/8000	1/6000	1/4000		1/3250	1/2000					1/1630
10.9	1.8	1/8000	1/6000	1/4000		1/3250	1/2000					1/1750
10.2	1.7	1/8000	1/6000	1/4000		1/3250	1/2000					1/1750
9.5	1.6	1/8000	1/6000	1/4000		1/3500	1/2000					1/1870
8.8	1.5	1/8000	1/6000	1/4000		1/3500						1/3500
8.2	1.4	1/8000	1/6000	1/4000		1/3500						1/3500
7.7	1.3	1/8000	1/6000	1/4000		1/3500						1/3500
7.2	1.2	1/8000	1/6000	1/4000		1/3500						1/3500
6.7	1.1	1/8000	1/6000	1/4000		1/3500						1/3500
6.3	1	1/8000	1/6000	1/4000		1/3500						1/3500
5.8	0.9	1/8000	1/6000	1/4000		1/3750						1/3750
5.4	0.8	1/8000	1/6000	1/4000		1/3750						1/3750
5.1	0.7	1/8000	1/6000	1/4000		1/4000						1/3250
4.7	0.6	1/8000	1/6000			1/4000						1/3500
4.4	0.5	1/8000	1/6000			1/4000						1/3750
4.1	0.4	1/8000	1/6000			1/4000						1/4000
3.8	0.3	1/8000	1/6000			1/4300						1/4300
3.6	0.2	1/8000	1/6000			1/4300						1/4300
3.3	0.1	1/8000	1/6000			1/4300						1/4300

bron color SCORO A4S : 閃光時間変動データ (2灯での変化)

SCORO A4S(ver.37.06) :3200Ws~3Ws

総出力	2灯使用:均等	1灯あたり Ws	閃光最短	選択範囲	選択範囲	選択範囲	選択範囲	選択範囲	閃光最適	選択範囲	選択範囲	選択範囲	閃光最長
10	9.0/9.0	1600	1/265						1/265				1/265
9.9	8.9/8.9	1493	1/265						1/250				1/250
9.8	8.8/8.8	1393	1/285						1/250				1/250
9.7	8.7/8.7	1300	1/350						1/250				1/250
9.6	8.6/8.6	1213	1/405						1/285				1/285
9.5	8.5/8.5	1131	1/465						1/325				1/325
9.4	8.4/8.4	1056	1/535					1/500	1/350				1/350
9.3	8.3/8.3	985	1/615					1/500	1/405			1/250	1/230
9.2	8.2/8.2	919	1/655					1/500	1/435			1/250	1/230
9.1	8.1/8.1	857	1/750					1/500	1/435			1/250	1/215
9	8.0/8.0	800	1/810						1/500	1/500	1/250		1/215
8.9	7.9/7.9	746	1/875						1/500		1/500	1/250	1/200
8.8	7.8/7.8	696	1/935						1/535		1/500	1/250	1/200
8.7	7.7/7.7	650	1/1070				1/1000		1/575		1/500	1/250	1/200
8.6	7.6/7.6	606	1/1150				1/1000		1/615		1/500	1/250	1/187
8.5	7.5/7.5	566	1/1230				1/1000		1/655		1/500	1/250	1/187
8.4	7.4/7.4	528	1/1310				1/1000		1/655		1/500	1/250	1/187
8.3	7.3/7.3	493	1/1400				1/1000		1/700		1/500	1/250	1/187
8.2	7.2/7.2	460	1/1500				1/1000		1/750		1/500	1/250	1/175
8.1	7.1/7.1	429	1/1630				1/1000		1/750		1/500	1/250	1/175
8	7.0/7.0	400	1/1750				1/1000		1/810		1/500	1/250	1/175
7.9	6.9/6.9	373	1/1870				1/1000		1/875		1/500	1/250	1/175
7.8	6.8/6.8	348	1/2000			1/2000	1/1000		1/875		1/500	1/250	1/175
7.7	6.7/6.7	325	1/2150			1/2000	1/1000		1/875		1/500	1/250	1/162
7.6	6.6/6.6	303	1/2300			1/2000	1/1000		1/935		1/500	1/250	1/162
7.5	6.5/6.5	283	1/2450			1/2000			1/1000	1/1000	1/500	1/250	1/162
7.4	6.4/6.4	264	1/2620			1/2000			1/1000	1/1000	1/500	1/250	1/162
7.3	6.3/6.3	246	1/2800			1/2000			1/1070	1/1000	1/500	1/250	1/162
7.2	6.2/6.2	230	1/3000			1/2000			1/1070	1/1000	1/500	1/250	1/162
7.1	6.1/6.1	214	1/3250			1/2000			1/1150	1/1000	1/500	1/250	1/150
7	6.0/6.0	200	1/3250			1/2000			1/1230	1/1000	1/500	1/250	1/150
6.9	5.9/5.9	187	1/3500			1/2000			1/1230	1/1000	1/500	1/250	1/150
6.8	5.8/5.8	174	1/3750			1/2000			1/1230	1/1000	1/500	1/250	1/150
6.7	5.7/5.7	162	1/4000		1/4000	1/2000			1/1230	1/1000	1/500	1/250	1/150
6.6	5.6/5.6	152	1/4300		1/4000	1/2000			1/1230	1/1000	1/500	1/250	1/140
6.5	5.5/5.5	141	1/4300		1/4000	1/2000			1/1230	1/1000	1/500	1/250	1/140
6.4	5.4/5.4	132	1/4600		1/4000	1/2000			1/1310	1/1000	1/500	1/250	1/140
6.3	5.3/5.3	123	1/4900		1/4000	1/2000			1/1310	1/1000	1/500	1/250	1/140
6.2	5.2/5.2	115	1/5250		1/4000	1/2000			1/1310	1/1000	1/500	1/250	1/132
6.1	5.1/5.1	107	1/5600		1/4000	1/2000			1/1310	1/1000	1/500	1/250	1/132
6	5.0/5.0	100	1/5600		1/4000	1/2000			1/1310	1/1000	1/500	1/250	1/132
5.9	4.9/4.9	93.3	1/6000	1/6000	1/4000	1/2000			1/1310	1/1000	1/500	1/250	1/132
5.8	4.8/4.8	87.1	1/6500	1/6000	1/4000	1/2000			1/1400	1/1000	1/500	1/250	1/125
5.7	4.7/4.7	81.2	1/6500	1/6000	1/4000	1/2000			1/1400	1/1000	1/500	1/250	1/140
5.6	4.6/4.6	75.8	1/7000	1/6000	1/4000	1/2000			1/1500	1/1000	1/500	1/250	1/175
5.5	4.5/4.5	70.7	1/7000	1/6000	1/4000	1/2000			1/1500	1/1000	1/500	1/250	1/187
5.4	4.4/4.4	66	1/7500	1/6000	1/4000	1/2000			1/1500	1/1000	1/500	1/250	1/215
5.3	4.3/4.3	61.6	1/8000	1/6000	1/4000	1/2000			1/1630	1/1000	1/500		1/250
5.2	4.2/4.2	57.4	1/8000	1/6000	1/4000	1/2000			1/1630	1/1000	1/500		1/265
5.1	4.1/4.1	53.6	1/8000	1/6000	1/4000	1/2000			1/1630	1/1000	1/500		1/305
5	4.0/4.0	50	1/8000	1/6000	1/4000	1/2000			1/1630	1/1000	1/500		1/325
4.9	3.9/3.9	46.7	1/8000	1/6000	1/4000	1/2000			1/1750	1/1000	1/500		1/350
4.8	3.8/3.8	43.5	1/8000	1/6000	1/4000	1/2000			1/1750	1/1000	1/500		1/405
4.7	3.7/3.7	40.6	1/8000	1/6000	1/4000	1/2000			1/1870	1/1000	1/500		1/435
4.6	3.6/3.6	37.9	1/8000	1/6000	1/4000	1/2000			1/1870	1/1000	1/500		1/465
4.5	3.5/3.5	35.4	1/8000	1/6000	1/4000	1/2000			1/1870	1/1000			1/500

bron color SCORO A4S : 閃光時間変動データ (2灯での変化)

SCORO A4S(ver.37.06) :3200Ws~3Ws

総出力	2灯使用:均等	1灯あたり Ws	閃光最短	選択範囲	選択範囲	閃光最適	選択範囲	選択範囲	選択範囲	閃光最長
4.4	3.4/3.4	33	1/8000	1/6000	1/4000	1/2000		1/2000	1/1000	1/535
4.3	3.3/3.3	30.8	1/8000	1/6000	1/4000	1/2000		1/2000	1/1000	1/575
4.2	3.2/3.2	28.7	1/8000	1/6000	1/4000	1/2150		1/2000	1/1000	1/615
4.1	3.1/3.1	26.8	1/8000	1/6000	1/4000	1/2150		1/2000	1/1000	1/655
4	3.0/3.0	25	1/8000	1/6000	1/4000	1/2150		1/2000	1/1000	1/700
3.9	2.9/2.9	23.3	1/8000	1/6000	1/4000	1/2300		1/2000	1/1000	1/750
3.8	2.8/2.8	21.8	1/8000	1/6000	1/4000	1/2300		1/2000	1/1000	1/810
3.7	2.7/2.7	20.3	1/8000	1/6000	1/4000	1/2450		1/2000	1/1000	1/875
3.6	2.6/2.6	18.9	1/8000	1/6000	1/4000	1/2450		1/2000	1/1000	1/935
3.5	2.5/2.5	17.7	1/8000	1/6000	1/4000	1/2620		1/2000		1/1000
3.4	2.4/2.4	16.5	1/8000	1/6000	1/4000	1/2800		1/2000		1/1000
3.3	2.3/2.3	15.4	1/8000	1/6000	1/4000	1/2800		1/2000		1/1070
3.2	2.2/2.2	14.4	1/8000	1/6000	1/4000	1/3000		1/2000		1/1150
3.1	2.1/2.1	13.4	1/8000	1/6000	1/4000	1/3000		1/2000		1/1230
3	2.0/2.0	12.5	1/8000	1/6000	1/4000	1/3250		1/2000		1/1310
2.9	1.9/1.9	11.7	1/8000	1/6000	1/4000	1/3250		1/2000		1/1400
2.8	1.8/1.8	10.9	1/8000	1/6000	1/4000	1/3250		1/2000		1/1400
2.7	1.7/1.7	10.2	1/8000	1/6000	1/4000	1/3250		1/2000		1/1500
2.6	1.6/1.6	9.5	1/8000	1/6000	1/4000	1/3250		1/2000		1/1630
2.5	1.5/1.5	8.8	1/8000	1/6000	1/4000	1/3250		1/2000		1/1630
2.4	1.4/1.4	8.2	1/8000	1/6000	1/4000	1/3500		1/2000		1/1750
2.3	1.3/1.3	7.7	1/8000	1/6000	1/4000	1/3500		1/2000		1/1750
2.2	1.2/1.2	7.2	1/8000	1/6000	1/4000	1/3500		1/2000		1/1870
2.1	1.1/1.1	6.7	1/8000	1/6000	1/4000	1/3500				1/3500
2	1.0/1.0	6.3	1/8000	1/6000	1/4000	1/3500				1/3500
1.9	0.9/0.9	5.8	1/8000	1/6000	1/4000	1/3750				1/3750
1.8	0.8/0.8	5.4	1/8000	1/6000	1/4000	1/3750				1/3750
1.7	0.7/0.7	5.1	1/8000	1/6000	1/4000	1/3750				1/3750
1.6	0.6/0.6	4.7	1/8000	1/6000		1/4000	1/4000			1/2450
1.5	0.5/0.5	4.4	1/8000	1/6000		1/4000	1/4000			1/2450
1.4	0.4/0.4	4.1	1/8000	1/6000		1/4300	1/4000			1/2620
1.3	0.3/0.3	3.8	1/8000	1/6000		1/4300	1/4000			1/2800
1.2	0.2/0.2	3.6	1/8000	1/6000		1/4600	1/4000			1/2800
1.1	0.1/0.1	3.3	1/8000	1/6000		1/4600	1/4000			1/3000

作成:21.12

bron color SCORO A4S : 閃光時間変動データ (3灯での変化)

SCORO A4S(ver.37.06) :3200Ws~3Ws

総出力	3灯使用:均等	1灯あたり Ws	閃光最短	選択範囲	選択範囲	選択範囲	閃光最適	選択範囲	選択範囲	閃光最長
10	8.4/8.4/8.4	1056	1/405				1/405			1/405
9.9	8.3/8.3/8.3	985	1/405				1/405			1/405
9.8	8.2/8.2/8.2	919	1/435				1/405			1/405
9.7	8.1/8.1/8.1	857	1/535			1/500	1/405			1/405
9.6	8.0/8.0/8.0	800	1/615			1/500	1/435			1/435
9.5	7.9/7.9/7.9	746	1/700				1/500		1/500	1/375
9.4	7.8/7.8/7.8	696	1/810				1/535		1/500	1/375
9.3	7.7/7.7/7.7	650	1/875				1/575		1/500	1/350
9.2	7.6/7.6/7.6	606	1/1000		1/1000		1/575		1/500	1/350
9.1	7.5/7.5/7.5	566	1/1070		1/1000		1/615		1/500	1/325
9	7.4/7.4/7.4	528	1/1150		1/1000		1/655		1/500	1/325
8.9	7.3/7.3/7.3	493	1/1310		1/1000		1/700		1/500	1/305
8.8	7.2/7.2/7.2	460	1/1400		1/1000		1/750		1/500	1/305
8.7	7.1/7.1/7.1	429	1/1500		1/1000		1/750		1/500	1/305
8.6	7.0/7.0/7.0	400	1/1630		1/1000		1/810		1/500	1/305
8.5	6.9/6.9/6.9	373	1/1750		1/1000		1/875		1/500	1/285
8.4	6.8/6.8/6.8	348	1/1870		1/1000		1/875		1/500	1/285
8.3	6.7/6.7/6.7	325	1/2000	1/2000	1/1000		1/935		1/500	1/285
8.2	6.6/6.6/6.6	303	1/2150	1/2000			1/1000	1/1000	1/500	1/285
8.1	6.5/6.5/6.5	283	1/2300	1/2000			1/1000	1/1000	1/500	1/265
8	6.4/6.4/6.4	264	1/2450	1/2000			1/1070	1/1000	1/500	1/265
7.9	6.3/6.3/6.3	246	1/2620	1/2000			1/1070	1/1000	1/500	1/265
7.8	6.2/6.2/6.2	230	1/2800	1/2000			1/1150	1/1000	1/500	1/265
7.7	6.1/6.1/6.1	214	1/3000	1/2000			1/1150	1/1000	1/500	1/250
7.6	6.0/6.0/6.0	200	1/3250	1/2000			1/1230	1/1000	1/500	1/250
7.5	5.9/5.9/5.9	187	1/3500	1/2000			1/1230	1/1000	1/500	1/250
7.4	5.8/5.8/5.8	174	1/3500	1/2000			1/1230	1/1000	1/500	1/250
7.3	5.7/5.7/5.7	162	1/3750	1/2000			1/1230	1/1000	1/500	1/250

bron color SCORO A4S : 閃光時間変動データ (3灯での変化)

SCORO A4S(ver.37.06) :3200Ws~3Ws

総出力	3灯使用:均等	1灯あたり Ws	閃光最短	選択範囲	選択範囲	選択範囲	閃光最適	選択範囲	選択範囲	選択範囲	選択範囲	閃光最長
7.2	5.6/5.6/5.6	152	1/4000		1/4000	1/2000	1/1230		1/1000	1/500		1/250
7.1	5.5/5.5/5.5	141	1/4300		1/4000	1/2000	1/1230		1/1000	1/500	1/250	1/230
7	5.4/5.4/5.4	132	1/4300		1/4000	1/2000	1/1230		1/1000	1/500	1/250	1/230
6.9	5.3/5.3/5.3	123	1/4600		1/4000	1/2000	1/1230		1/1000	1/500	1/250	1/230
6.8	5.2/5.2/5.2	115	1/4900		1/4000	1/2000	1/1230		1/1000	1/500	1/250	1/230
6.7	5.1/5.1/5.1	107	1/5250		1/4000	1/2000	1/1230		1/1000	1/500	1/250	1/215
6.6	5.0/5.0/5.0	100	1/5250		1/4000	1/2000	1/1230		1/1000	1/500	1/250	1/230
6.5	4.9/4.9/4.9	93.3	1/5600		1/4000	1/2000	1/1310		1/1000	1/500	1/250	1/215
6.4	4.8/4.8/4.8	87.1	1/6000	1/6000	1/4000	1/2000	1/1310		1/1000	1/500	1/250	1/215
6.3	4.7/4.7/4.7	81.2	1/6500	1/6000	1/4000	1/2000	1/1400		1/1000	1/500	1/250	1/215
6.2	4.6/4.6/4.6	75.8	1/6500	1/6000	1/4000	1/2000	1/1400		1/1000	1/500	1/250	1/215
6.1	4.5/4.5/4.5	70.7	1/7000	1/6000	1/4000	1/2000	1/1400		1/1000	1/500	1/250	1/215
6	4.4/4.4/4.4	66	1/7000	1/6000	1/4000	1/2000	1/1500		1/1000	1/500	1/250	1/200
5.9	4.3/4.3/4.3	61.6	1/7500	1/6000	1/4000	1/2000	1/1500		1/1000	1/500	1/250	1/200
5.8	4.2/4.2/4.2	57.4	1/8000	1/6000	1/4000	1/2000	1/1630		1/1000	1/500	1/250	1/200
5.7	4.1/4.1/4.1	53.6	1/8000	1/6000	1/4000	1/2000	1/1630		1/1000	1/500	1/250	1/200
5.6	4.0/4.0/4.0	50	1/8000	1/6000	1/4000	1/2000	1/1630		1/1000	1/500	1/250	1/200
5.5	3.9/3.9/3.9	46.7	1/8000	1/6000	1/4000	1/2000	1/1750		1/1000	1/500		1/250
5.4	3.8/3.8/3.8	43.5	1/8000	1/6000	1/4000	1/2000	1/1750		1/1000	1/500		1/285
5.3	3.7/3.7/3.7	40.6	1/8000	1/6000	1/4000	1/2000	1/1750		1/1000	1/500		1/325
5.2	3.6/3.6/3.6	37.9	1/8000	1/6000	1/4000	1/2000	1/1870		1/1000	1/500		1/375
5.1	3.5/3.5/3.5	35.4	1/8000	1/6000	1/4000	1/2000	1/1870		1/1000	1/500		1/405
5	3.4/3.4/3.4	33	1/8000	1/6000	1/4000		1/2000	1/2000	1/1000	1/500		1/465
4.9	3.3/3.3/3.3	30.8	1/8000	1/6000	1/4000		1/2000	1/2000	1/1000			1/500
4.8	3.2/3.2/3.2	28.7	1/8000	1/6000	1/4000		1/2000	1/2000	1/1000			1/535
4.7	3.1/3.1/3.1	26.8	1/8000	1/6000	1/4000		1/2150	1/2000	1/1000			1/615
4.6	3.0/3.0/3.0	25	1/8000	1/6000	1/4000		1/2150	1/2000	1/1000			1/655
4.5	2.9/2.9/2.9	23.3	1/8000	1/6000	1/4000		1/2300	1/2000	1/1000			1/700
4.4	2.8/2.8/2.8	21.8	1/8000	1/6000	1/4000		1/2300	1/2000	1/1000			1/750
4.3	2.7/2.7/2.7	20.3	1/8000	1/6000	1/4000		1/2450	1/2000	1/1000			1/810
4.2	2.6/2.6/2.6	18.9	1/8000	1/6000	1/4000		1/2620	1/2000	1/1000			1/875
4.1	2.5/2.5/2.5	17.7	1/8000	1/6000	1/4000		1/2800	1/2000				1/1000
4	2.4/2.4/2.4	16.5	1/8000	1/6000	1/4000		1/2800	1/2000				1/1070
3.9	2.3/2.3/2.3	15.4	1/8000	1/6000	1/4000		1/3000	1/2000				1/1150
3.8	2.2/2.2/2.2	14.4	1/8000	1/6000	1/4000		1/3000	1/2000				1/1230
3.7	2.1/2.1/2.1	13.4	1/8000	1/6000	1/4000		1/3250	1/2000				1/1310
3.6	2.0/2.0/2.0	12.5	1/8000	1/6000	1/4000		1/3500	1/2000				1/1400
3.5	1.9/1.9/1.9	11.7	1/8000	1/6000	1/4000		1/3500	1/2000				1/1500
3.4	1.8/1.8/1.8	10.9	1/8000	1/6000	1/4000		1/3500	1/2000				1/1630
3.3	1.7/1.7/1.7	10.2	1/8000	1/6000	1/4000		1/3500	1/2000				1/1630
3.2	1.6/1.6/1.6	9.5	1/8000	1/6000	1/4000		1/3500	1/2000				1/1750
3.1	1.5/1.5/1.5	8.8	1/8000	1/6000	1/4000		1/3500	1/2000				1/1750
3	1.4/1.4/1.4	8.2	1/8000	1/6000	1/4000		1/3500	1/2000				1/1870
2.9	1.3/1.3/1.3	7.7	1/8000	1/6000	1/4000		1/3500	1/2000				1/1870
2.8	1.2/1.2/1.2	7.2	1/8000	1/6000	1/4000		1/3500					1/3500
2.7	1.1/1.1/1.1	6.7	1/8000	1/6000	1/4000		1/3500					1/3500
2.6	1.0/1.0/1.0	6.3	1/8000	1/6000	1/4000		1/3500					1/3500
2.5	0.9/0.9/0.9	5.8	1/8000	1/6000	1/4000		1/3500					1/3500
2.4	0.8/0.8/0.8	5.4	1/8000	1/6000	1/4000		1/3750					1/3750
2.3	0.7/0.7/0.7	5.1	1/8000	1/6000	1/4000		1/3750					1/3750
2.2	0.6/0.6/0.6	4.7	1/8000	1/6000	1/4000		1/3750					1/3750
2.1	0.5/0.5/0.5	4.4	1/8000	1/6000	1/4000		1/3750					1/3750
2	0.4/0.4/0.4	4.1	1/8000	1/6000			1/4000					1/2450
1.9	0.3/0.3/0.3	3.8	1/8000	1/6000			1/4000					1/2450
1.8	0.2/0.2/0.2	3.6	1/8000	1/6000			1/4000					1/2450
1.7	0.1/0.1/0.1	3.3	1/8000	1/6000			1/4000					1/2620